

POLY-COAT Putty 3300

Description:

POLY-COAT Putty 3300 is a water-borne high grade quality heavy bodied oil-latex blockfiller. Designed to fill voids and reduce irregularities on almost all interior masonry surfaces. based on acrylic resins, linseed oil, fine graded fillers and special additives.

Area of Use:

POLY-COAT Putty 3300 is designed to be used on woodworks, block concrete, cinder block, pumice block and other types of masnry, where an attractive smooth surface is desired.

Technical Data:

Specific Gravity	: 1, 72 ± 0, 02.	Thinning	: N.A.
Viscosity	: 150 gm/cm.	Wash ability	: N.A.
Solid by volume	: 49,0 ± 0, 5%	Mode of application	: Trowel, Spatula knife or spray.
Colors	: White.	Drying for touching	: 30 min @ 25 °C & 50% R.H. (500 microns).
Finish	: Smooth & Matt.	Drying for recoating	: 2 hours @ 25 °C & 50% R.H. (500 microns).
Coverage	: 2,33 m ² /Kg @ 250 microns wft.	Cleaning of tools	: Clean water.
pH	: 8, 5 – 9.0.	Storage	: 2 years from date of production.
Flash Point	: Not Flammable.		

Surfaces Preparation:

The substrate to be filled should be suitably dry, clean, free from loose material, dust, grease, oil and any other contamination. Treat any areas affected by mould, lichens, algae and moss with fungicidal solution. Confirm that the correct surface preparation and pre-treatment is carried out.

Internal Surfaces:

- Stir thoroughly before use. Thin SIPES Binder Sealer with clean water up to 30% for friable or chalky surfaces to achieve a deeper penetration possible, 20% for firm surfaces.
- Apply one or two full layer, or patch imperfection and wall irregularity with **Poly-Coat Putty 3300**.
- Touchup with SIPES Primer Sealer All areas repaired with putty prior to application of topcoats.
- Apply two coats of conventional solvent or water-based architectural finish.

External Surfaces:

- Not recommended.

Packing:

Available in 20 Kg/Pail.

General Information:

- Store in a cool, dry and ventilated place. Keep container closed when not in use.
- Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.
- Ensure good ventilation and use mask and safety gloves while applying.
- Do not apply when there is a risk of rain, air or substrate temperatures are likely to fall below 8 °C or when the relative humidity is above 80% during application or the drying period.

Health and Safety:

- When preparing all surfaces avoid the inhalation of dust.
- In case of eye contact, flush with plenty of water and consult a doctor. If swallowed seek medical attention immediately.
- Keep away from food, children and animals.
- Do not empty into sewer, watercourses or access routes to septic tanks.

Due to standards and specification evolution, the company reserves the right to change the given data without prior notification.

Universal Paints Manufacturing Co. Ltd. Industrial City, Phase 03, Kingdom of Saudi Arabia
Tel: +966 2 2686999 Fax: +966 2 6389680 Po.Box: 16945, Jeddah: 21474

