

# SI-TONE

## Morino White 1850

### **Description:**

**SI-TONE Morino White 1850** is a water-borne high quality coating based on acrylic copolymer emulsion and selected graded marble chips. It has good adhesion, weather and water resistant properties, adds more protection and beauty to your properties.

### **Area of Use:**

**SI-TONE Morino White 1850** is designed to be used on almost all exterior and interior surfaces, where an attractive ancient look antique effects texture finish is desired.

### **Technical Data:**

Specific Gravity	: 1, 8 ± 0, 1.	Thinner	: Water
Viscosity	: 150 gm/cm.	Thinning	: N.A.
Solid by volume	: 55 ± 0, 5%.	Wash ability	: Very Good.
Colors	: White.	Mode of application	: Spatula, Trowel, Spray, Stamp pad
Finish	: Smooth Grain & Matt.	Surface Drying	: 60 min @ 25 °C.
Coverage	: 0.59-1.1m <sup>2</sup> /Kg@ 500microns wft.	Dry to Recoat	: Over night @ 25 °C.
pH	: 8, 5 – 9.0.	Cleaning of tools	: Clean water.
Flash Point	: Not Flammable.	Storage	: 2 years from date of production.

### **Surfaces Preparation:**

The substrate to be coated should be suitably dry, clean, free from loose material, dust, grease, oil and any other contamination. Treat any areas affected by mould, lichens, algae and moss with fungicidal solution. Confirm that the correct surface preparation and pre-treatment is carried out.

Internal & External Surfaces			
Product	Description	Product	Description
<b>SI-TONE Morino White 1850</b>	Patching, irregularity	<i>Toskana Pearl 5400 Series</i>	<i>Or 1 Top Coat</i>
<b>SI-TONE Morino White 1850</b>	<b>1 Coat</b>	<i>SI-TONE Clear Glaze 475</i>	<i>Or 1 Top Coat</i>
<b>SI-TONE Morino White 1850</b>	<b>1 Coat</b>	<i>Thermoacrylic TopCoat 800</i>	<i>Or 2 Top Coat</i>
<i>DecoAntico 5000</i>	<i>1 Top Coat</i>	<i>And any other paint</i>	<i>Or 2 Top Coat</i>

### **Packing:**

Available in **15 Liters/Pail**.

### **General Information:**

- Store in a cool, dry and ventilated place. Keep container closed when not in use.
- Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.
- Ensure good ventilation and use mask and safety gloves while applying.
- Do not apply when there is a risk of rain, air or substrate temperatures are likely to fall below 8 °C or when the relative humidity is above 80% during application or the drying period.

### **Health and Safety:**

- When preparing all surfaces avoid the inhalation of dust.
- In case of eye contact, flush with plenty of water and consult a doctor. If swallowed seek medical attention immediately.
- Keep away from food, children and animals.
- Do not empty into sewer, watercourses or access routes to septic tanks.

Due to standards and specification evolution, the company reserves the right to change the given data without prior notification.

<b>Universal Paints Manufacturing Co. Ltd.</b> Industrial City, Phase 03, Kingdom of Saudi Arabia Tel: +966 2 2686999 Fax: +966 2 6389680 Po.Box: 16945, Jeddah: 21474	 
---	---