



Wash Primer - N° 476

PRODUCT TYPE :	An outstanding tough, anti- corrosive etch primer based on Vinyl Butural Copolymer Resin.	
AREAS OF USE :	It is used on non ferrous metals, aluminium gladding, galvanized surfaces, brass and the like.	
SURFACE PREPARATION:	Surfaces to be primed must be free of dust, dirt and oil to secure sufficient adhesion.	
APPLICATION METHODS:	Brush / Roller Diluted up to 20% with thinner. Airless Spray Gun Diluted up to 30% with thinner. Pot life of mixture : up to 8 hours.	
SAFETY MEASURE:	Avoid inhalation of spray mist vapors. The area should be properly ventilated. It is recommended to use mask when spraying.	
PACKING SIZE:	1/4 US Gallon	0.946 ltr.
	1 US Gallon	3.785 ltr.
VALIDITY:	2 Years from the date of production	

The technical data sheet for use contained herein are correct to the best of our knowledge. However, as conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality. All technical information is subject to change without prior notice.

Color:	Yellow	Theoretical Coverage:	40 m ² /U.S.Gal @ 10 µmD.F.T
Binder:	Vinyl Butural	Drying time:	To Touch: 30 min
Finish:	Mat		To Recoat: 2 hrs
Solvent:	Thinner N° 280	Solids:	By Weight 20%
Viscosity:	68/72 KU's @ 25°C		By Volume 10%
Density:	0.9 kg/lit	VOC Content:	400 g/l