

Duralac Thermoacrylic Fluorescent Paint 850

Description:

Superior quality acrylic resin coating with light fast pigments. Excellent weather and pollution resistance. It gives gloss finish and non yellowing characteristic. Good for coastal, industrial zones and aggressive environment. It has excellent UV resistance .

Colors:

Available in yellow.

Packing:

Available in 1 ltr, 1 USG and 18 Liter drum.

Area of Use:

Duralac thermoacrylic top coat can be applied on most types of surfaces. It gives durable protection and easy to clean surfaces. It is recommended for internal and external surfaces of concrete, steel and gypsum boards. When applied on textures it gives glossy finish, protection and less dust accumulation with easy cleaning .

Technical Data:

Specific Gravity	: 1.150	Thinner	: Acrylic thinner
Viscosity	: 78 KU	Thinning	: 15 – 20%
Solid by volume	: 37±2%	Washability	: Very good
Finish	: Gloss	Mode of application	: Roller, spray, brush
Coverage	: 10.5M ² /ltr@35μ dft	Cleaning of tools	: Tool cleaner
Drying time for touching	: 20 minutes	Storage	: Room temperature
Drying time for Recoating	: 4 hrs	Flash Point	: 38 °C

Surfaces Preparation:

Plastered surfaces to be clean and free from all contaminations. Scrub the surface with sand paper or sanding stone. All other surfaces to be clean from dust and other foreign material.

New Surfaces:

Clean the surface from dust, dirt and loose particles.
Apply one coat of Duralac Penetrating Primer Sealer 421 for cementitious surface.

Repaintings:

For previously painted Glossy surfaces sand properly order to get the best adhesion between the two coats.

Precautions:

1. Store in a cool, dry and ventilated place. Keep container closed when not in use.
2. Ensure good ventilation and use mask and safety gloves while applying.
3. Do not inhale. In case of eye contact, flush with plenty of water and consult a doctor. If swallowed seek medical attention immediately.

Safety for Use:

- Keep away from food.
- Do not empty into sewer.
- Keep away from children.

Due to standards and specification evolution, the company reserves the right to change the given data without prior notification.

Universal Paints Manufacturing Co. Ltd. Industrial City, Phase 03, Kingdom of Saudi Arabia
Tel: +966 2 2686999 Fax: +966 2 6389680 Po.Box: 16945, Jeddah: 21474

